MINI" LOW CURRENT FLOAT

FOR CONTROL PANELS
LOW CURRENT NARROW-ANGLE

OVERVIEW

The PRIMEX® MINI™ narrow angle mechanically-activated control switches are designed to activate **low current** control panels and alarms. These control switches offer reliable control for water, wastewater, and similar applications. The internal switching mechanism has sealed gold cross-point contacts for reliable low current operation.

PART NUMBERS

Blue Cap Floats:

- **1039250** 50' flexible SJOW water resistant cable, external weight for mounting; **normally open contacts**
- 1039911 75' flexible SJOW water resistant cable, external weight for mounting; normally open contacts
- 1039913 100' flexible SJOW water resistant cable, external weight for mounting; normally open contacts

Red Cap Floats:

- **1039910** 50' flexible SJOW water resistant cable, external weight for mounting; **normally closed contacts**
- 1039912 75' flexible SJOW water resistant cable, external weight for mounting; normally closed contacts
- 1039914 100' flexible SJOW water resistant cable, external weight for mounting; normally closed contacts

Green Cap Floats:

- 1041658 50' flexible SJOW water resistant cable, external weight for mounting; SPDT normally open or normally closed contacts
- 1041659 75' flexible SJOW water resistant cable, external weight for mounting; SPDT normally open or normally closed contacts
- 1041660 100' flexible SJOW water resistant cable, external weight for mounting; SPDT normally open or normally closed contacts



*Float brackets sold separately

APPLICATIONS

- Low current control panels and alarms
- PLC (Programmable Logic Controller) panels
- Panels with intrinsically safe barriers

ELECTRICAL RATINGS

Maximum Electrical Load

- 1 Amp 125 VAC
- 1 Amp 30 VDC

Minimum Electrical Load

- 0.160 mA 125 VAC
- 0.160 mA 30 VDC
- 1 mA 5 VDC

Contact your PRIMEX® dealer for pricing and availability today!

